

Hefei TNJ Chemical Industry Co.,Ltd.

D1508 Xincheng Business Center, Qianshan Rd. Hefei 230022 China

Tel: (0086) 551 5418678
Fax: (0086) 551 5418697
Email: info@tnjchem.com
Site: www.tnjchem.com

Material Safety Data Sheet

Benzoyl chloride MSDS

Section 1: Chemical Product and Company Identification

Product name: Benzoyl chloride
Molecular formula:C7H5CIO

CAS No.: 98-88-4 **RTECS:** DM6600000

TSCA: TSCA 8(b) inventory: Benzoyl chloride

Synonyms: BENZOIC ACID CHLORIDE

Contact Information for Emergency: (0086) 551 5418696

Hefei TNJ Chemical Industry Co., Ltd.

B911 Xincheng Business Center

Qianshan Road, Hefei

Tel: (0086) 551 5418695

Fax: (0086) 551 5418697

Email: info@tnjchem.com

China

Site: www.tnjchem.com

Section 2: Composition and Information on Ingredients

Composition:

Name CAS # % by Weight

Benzoyl chloride 98-88-4 100

Toxicological Data on Ingredients: Benzoyl chloride LD50: Not available. LC50: Not available.

Section 3: Hazards Identification

Potential Acute Health Effects:

Extremely hazardous in case of skin contact (corrosive, irritant), of eye contact (irritant), of ingestion, of inhalation. Very hazardous in case of skin contact (sensitizer, permeator). Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

Potential Chronic Health Effects:

Extremely hazardous in case of skin contact (corrosive, irritant), of eye contact (irritant), of ingestion, of inhalation.

Veryhazardous in case of skin contact (sensitizer, permeator). CARCINOGENIC EFFECTS: Not available. MUTAGENIC

EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to lungs, mucous membranes. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation.

Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection. Repeated or prolonged inhalation of vapors may lead to chronic respiratory irritation.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin Contact:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: Combustible.

Auto-Ignition Temperature: 197° C (386.6° F)

Flash Points: CLOSED CUP: 72° C (161.6° F).

Flammable Limits: LOWER: 1.2% UPPER: 4.9%

Products of Combustion: These products are carbon oxides (CO, CO2).

Fire Hazards in Presence of Various Substances: Not available.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product

in presence of static discharge: Not available.

Fire Fighting Media and Instructions:

SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Special Remarks on Fire Hazards: Not available.

Special Remarks on Explosion Hazards: Not available.

Section 6: Accidental Release Measures

Small Spill: Absorb with an inert material and put the spilled material in an appropriate waste disposal.

Large Spill:

Combustible material. Corrosive liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk.

Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed.

Call for assistance on disposal.

Section 7: Handling and Storage

Precautions:

Keep container dry. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Never add water to this product. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes.

Storage:

Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection:

Face shield. Full suit. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves. Boots.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits: Not available.

Section 9: Physical and Chemical Properties

Physical state and appearance: Liquid. (Fuming liquid.)

Odor: Pungent.

Taste: Not available.

Molecular Weight: 140.57 g/mole

Color: Colorless.

pH (1% soln/water): Not available.

Boiling Point: 197.2° C (387° F)

Melting Point: -1° C (30.2° F)

Critical Temperature: Not available.

Specific Gravity: 1.2188 (Water = 1)

Vapor Pressure: 0.1 kPa (@ 20° C)

Vapor Density: 4.88 (Air = 1)

Volatility: Not available.

Odor Threshold: Not available.
Water/Oil Dist. Coeff.: Not available.
Ionicity (in Water): Not available.
Dispersion Properties: Not available.

Solubility: Not available.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available. **Conditions of Instability:** Not available.

Incompatibility with various substances: Not available.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity: Not available.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Dermal contact. Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE.

Acute toxicity of the vapor (LC50): 1870 1 hours [Rat].

Chronic Effects on Humans: Causes damage to the following organs: lungs, mucous membranes.

Other Toxic Effects on Humans:

Extremely hazardous in case of skin contact (corrosive, irritant), of eye contact (corrosive), of ingestion, of inhalation (lung corrosive). Very hazardous in case of skin contact (sensitizer, permeator).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Not available.

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may

arise.

Toxicity of the Products of Biodegradation: The products of degradation are more toxic.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Section 14: Transport Information

DOT Classification: Class 8: Corrosive material

Identification: Benzoyl Chloride UNNA: UN1736 PG: II **Special Provisions for Transport:** Not available.

Section 15: Other Regulatory Information

Federal and State Regulations:

Pennsylvania RTK: Benzoyl chloride Massachusetts RTK: Benzoyl chloride TSCA 8(b) inventory: Benzoyl chloride SARA 313 toxic chemical notification and release reporting: Benzoyl chloride CERCLA: Hazardous substances.:

Benzoyl chloride

Other Regulations: OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications:

WHMIS (Canada):

CLASS B-3: Combustible liquid with a flash point between 37.8° C (100° F) and 93.3° C (200° F). CLASS D-1A: Material causing immediate and serious toxic effects (VERY TOXIC). CLASS D-2A: Material causing other toxic effects (VERY TOXIC). CLASS E: Corrosive liquid.

DSCL (EEC):

R20- Harmful by inhalation. R35- Causes severe burns. R43- May cause sensitization by skin contact.

HMIS (U.S.A.): Health Hazard: 2 Fire Hazard: 2 Reactivity: 0

Personal Protection:

National Fire Protection Association (U.S.A.):

Health: 2

Flammability: 2 Reactivity: 2 Specific hazard:

Protective Equipment:

Gloves. Full suit. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Face shield.

Section 16: Other Information

References: Not available.

Other Special Considerations: Not available.

Created: 10/10/2005 08:14 PM

Last Updated: 05/21/2016 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we are liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if we has been advised of the possibility of such damages.